



RAPID CONTROL SERVICE, INC.

Partners In Automation Since 1964

PNEUMATIC / ELECTRICAL / RESISTANCE WELDING

Phone: 616-538-1111

WATTS: 1-800-632-1857

Fax: 616-538-6847

Website: www.rapidcontrol.com

E-Mail: sales@rapidcontrol.com

QUICK DISCONNECTS UNIVERSAL COULPER



1/4 Basic Size

- Automatic Coupler
- Brass Body, NBR Seal
- Stainless Steel Spring
- Steel Locking Balls
- Good For Low Pressure

Industrial



Parker



ARO



28-589

Working Range:

- Maximum Operation Pressure
220psi
- Temperature: -4° to 176°F

Industrial Interchange

Sleeve type couplings are widely used to connect compressed air. Their compact and economical design uses a ball locking mechanism consisting of captive steel balls that engage the locking groove on the mating nipple. The sliding spring loaded sleeve on the coupler must be manually retracted in order to connect or disconnect the nipple. This is easy to do.

Part #		Size	Price
28-589	Coupler	3/8 NPT	\$9.68

Plugs

Part #		Size	Price
1802	Male Plug	1/8 NPT	\$1.30
1804	Male Plug	1/4 NPT	\$1.12
1806	Male Plug	3/8 NPT	\$1.72
1805	Female Plug	1/4 NPT	\$1.29

2479 28th Street • Grand Rapids, MI • 49519